



# SAFETY DATA SHEET

# AKB500OIL

## 1. CHEMICAL PRODUCT AND COMPANY INFORMATION

**PRODUCT:** ALKYL BENZENE 500

**PRODUCT CODE:** AKB500E

**CHEMICAL NAME/FAMILY:** ALKYL BENZENE

**OTHER NAME:** REFRIGERANT OIL

**MANUFACTURER / DISTRIBUTOR:** NATIONAL REFRIGERANTS, INC.

**ADDRESS:** 11401 ROOSEVELT BOULEVARD PHILA., PA. 19154

**INFORMATION:** 800-262-0012

**EMERGENCY:** 800-424-9300

**DATE:** 1/2015

**PREPARER:** Matt Callahan

## 2. HAZARD IDENTIFICATION

**CLASSIFICATION:** Not classified according to 29 CFR 1910.1200 (2012)

**OTHER HAZARDS:** SKIN AND EYE CONTACT: Prolonged contact may cause minor skin irritation.

## 3. COMPOSITION/ INFORMATION ON INGREDIENTS

<u>INGREDIENT</u>	<u>CAS#</u>	<u>WEIGHT</u>
Synthetic Lubricant	Proprietary	100%
*no hazardous ingredients		

### COMMON NAMES AND SYNONYMS

Synthetic Refrigerant Oil

There are no stabilizers or impurities that contribute to the classification of the material identified in section 2

## 4. FIRST AID MEASURES

**EYES:** Immediately flush eyes with plenty of water for at least 15 minutes while holding the eyelids open. If irritation persists, see a physician.

**SKIN CONTACT:** Remove contaminated clothing. Wash skin thoroughly with soap and water. Launder contaminated clothing. See a doctor if irritation persists.

**INHALATION:** Remove to fresh air. If not breathing, give artificial respiration and seek medical attention immediately.



# **SAFETY DATA SHEET**

# **AKB500OIL**

**INGESTION:** If swallowed, call a physician immediately. ONLY induce vomiting at the instruction of a physician. Never give anything by mouth to an unconscious person. If medical advice cannot be obtained, take the person, product container and MSDS to the nearest medical emergency center.

## **5. FIRE FIGHTING MEASURES**

### **RECOMMENDED FIRE EXTINGUISHING AGENTS AND SPECIAL PROCEDURES:**

Use water spray, dry chemical, foam, or carbon dioxide to extinguish flames. Use water spray to cool fire-exposed containers. Water or foam may cause frothing.

**SPECIAL PROTECTIVE EQUIPMENT FOR FIREFIGHTERS:** Wear full protective clothing and positive pressure breathing apparatus. Use water carefully near exposed liquid to avoid frothing and splashing of hot liquid.

**UNUSUAL OR EXPLOSIVE HAZARDS:** None

## **6. ACCIDENTAL RELEASE MEASURES**

### **PROCEDURES IN CASE OF ACIDENTAL RELEASE, BREAKAGE OR LEAKAGE:**

Ventilate area. Avoid breathing vapor. Wear appropriate personal protective equipment, including appropriate respiratory protection. Contain spill if possible. Wipe up or absorb on suitable material and shovel up. Prevent entry into sewers and waterways. Avoid contact with skin, eyes or clothing.

## **7. HANDLING AND STORAGE**

**HANDLING:** Minimum feasible handling temperatures should be maintained. Avoid exposure to heat and flames. Protect against eye and skin contact.

**STORAGE:** Periods of exposure to high temperatures should be minimized. Water contamination should be avoided. Keep container tightly sealed when not in use. Store containers in an upright and secure position to prevent spills and protect against damage.

## **8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

**ENGINEERING CONTROLS:** Local exhaust ventilation recommended if generating vapor, dust, or mist. If exhaust ventilation is not available or inadequate, use NIOSH approved respirator as appropriate.

### **PROTECTIVE EQUIPMENT (TYPE)**

#### **EYE/FACE PROTECTION:**

Safety glasses, chemical type goggles, or face shield recommended to prevent eye contact.



# SAFETY DATA SHEET

# AKB500OIL

**SKIN PROTECTION:** Protective clothing such as coveralls or lab coats should be worn. Launder or dry-clean when soiled. Gloves and boots resistant to chemicals and petroleum distillates required. Exposed workers should wash exposed skin several times daily with soap and water.

Remove and dry-clean or launder clothing soaked or soiled with this material before reuse. Dry cleaning of contaminated clothing may be more effective the normal laundering. Inform individuals responsible for cleaning of the potential hazards associated with handling contaminated clothing.

**RESPIRATORY PROTECTION:** Airborne concentrations should be kept to lowest levels possible. If vapor, dust or mist is generated and the occupational exposure limit of the product, or any component of the product, is exceeded, use appropriate NIOSH or MSHA approved air purifying or air-supplied respirator after determining the airborne concentration of the contaminant.

Air supplied respirators should always be worn when airborne concentration of the contaminant or oxygen content is unknown.

**EXPOSURE GUIDELINES:** ACGIH TLV = 5mg/m<sup>3</sup>

## 9. PHYSICAL AND CHEMICAL PROPERTIES

<b>APPEARANCE:</b>	Clear to amber liquid
<b>ODOR:</b>	Odorless
<b>ODOR THRESHOLD:</b>	Not determined
<b>PH:</b>	Not applicable
<b>MELTING POINT/FREEZING POINT:</b>	Not determined
<b>BOILING POINT:</b>	>300° F
<b>FLASH POINT: COC METHOD</b>	200°C (392°F)
<b>EVAPORATION RATE:</b>	Nil
<b>FLAMMABILITY:</b>	Not applicable
<b>LEL/UEL:</b>	Not applicable
<b>VAPOR PRESSURE:</b>	<0.01 mmHg @ 20 deg. C
<b>VAPOR DENSITY:</b>	Not determined
<b>RELATIVE DENSITY:</b>	.86 (water = 1.0)
<b>SOLUBILITY:</b>	Insoluble
<b>PARTITION COEFFICIENT n-Octanol/water:</b>	Not determined
<b>AUTO IGNITION TEMPERATURE:</b>	Not Determined
<b>DECOMPOSITION TEMPERATURE:</b>	360°C (680°F)
<b>VISCOSITY:</b>	98 cSt at 40°C

## 10. STABILITY AND REACTIVITY

**STABILITY:** Stable (thermal, light)



# SAFETY DATA SHEET

# AKB500OIL

**INCOMPATIBILITY:** May react with strong oxidizing materials.

**HAZARDOUS POLYMERIZATION:** Will not occur.

**HAZARDOUS DECOMPOSITION PRODUCTS:** Normal combustion forms carbon dioxide and water vapor; incomplete combustion can produce carbon monoxide.

## 11. TOXICOLOGICAL INFORMATION

### TOXICOLOGICAL INFORMATION (ANIMAL TOXICITY DATA)

**ORAL:** LD50 believed to be >5 g/kg (rat) practically non-toxic

**INHALATION:** Not determined; not expected to be an inhalation hazard.

**DERMAL:** LD50 believed to be >5 g/kg (rabbit) practically non-toxic.

### IRRITATION INDEX, ESTIMATION OF IRRITATION (SPECIES)

**SKIN:** (Draize) believed to be between 3-5 (rabbit) moderately irritating (maximum 8)

**EYES:** (Draize) believed to be <15 (rabbit) no appreciable effect (maximum 110)

**SENSITIZATION:** Not determined

### POTENTIAL HEALTH EFFECTS:

PRIMARY ROUTE OF EXPOSURE: Skin

### EFFECTS OF OVEREXPOSURE:

**EYES:** Expected to cause no more than minor eye irritation. Application of a similar product into the eyes of rabbits produced very slight membrane irritation without corneal injury. Avoid eye contact as good industrial practice.

**SKIN:** Not a primary skin irritant but may cause skin irritation on repeated or prolonged contact. Application of a similar product onto the skin of rabbits produced slight erythmia and edema

**INGESTION:** May cause nausea. Not expected to be acutely toxic by ingestion.

**INHALATION:** Avoid breathing vapor or mist. Under normal use conditions, this product is not an inhalation hazard. Prolonged exposure to vapors may cause dizziness and headaches.

There is no evidence that this product aggravates and existing medical condition.

**OTHER:** This product, or a component of this product, has been shown to damage red blood cells or blood forming organs, and has caused anemia in laboratory animals.

## 12. ECOLOGICAL INFORMATION

96 hr. LC50 Rainbow Trout (*Salmo gairdneri*) >1000mg/L practically non-toxic.

96 hr. LC50 Sheepshead Minnow (*Cyprinodon variegatus*) >1000mg/L practically non-toxic.



# SAFETY DATA SHEET

# AKB500OIL

Biodegradability: Estimated to be less than 40% degradation over a test period of more than 28 days.

Potential to Bioaccumulation: This product is estimated to have a very slow rate of bioaccumulation.

## **13. DISPOSAL CONSIDERATIONS**

**WASTE DISPOSAL METHODS:** This product has been evaluated for RCRA characteristics and does not meet the criteria of a hazardous waste if discarded in its purchased form. Under RCRA, it is the responsibility of the user of the product to determine at the time of disposal, whether the product meets RCRA criteria for hazardous waste. This is because product uses, transformations, mixtures, processes, etc. may render the resulting materials hazardous.

## **14. TRANSPORTATION INFORMATION**

**DOT:** Not regulated by DOT.

## **15. REGULATORY INFORMATION**

### **FEDERAL REGULATIONS:**

This product and/or its components are considered non-hazardous by the following standards:  
OSHA Hazard Communication Classification

## **16. OTHER INFORMATION**

<b>HMIS</b>	<b>H</b>	<b>F</b>	<b>R</b>
	<b>0</b>	<b>1</b>	<b>0</b>

### **DISCLAIMER**

INFORMATION AND RECOMMENDATIONS CONTAINED HEREIN ARE BELIEVED TO BE ACCURATE AT THE TIME OF PREPARATION. NO WARRANTY IS MADE CONCERNING THE ACCURACY AND NO LIABILITY SHALL BE MADE FOR CLAIMS FOR USE OR RELIANCE OF THE RECOMMENDATIONS CONTAINED HEREIN