



SAFETY DATA SHEET

VPO

1. CHEMICAL PRODUCT AND COMPANY INFORMATION

PRODUCT: NATIONAL VACUUM PUMP OIL

PRODUCT CODE: VPO

CHEMICAL NAME/FAMILY: PETROLEUM LUBRICATING OIL

OTHER NAME: VACUUM PUMP OIL

MANUFACTURER: NATIONAL REFRIGERANTS, INC.

ADDRESS: 11401 Roosevelt Boulevard Phila., Pa. 19154

INFORMATION: 800-262-0012

EMERGENCY: 800-424-9300

DATE: 01/2021

PREPARER: Matt Callahan

2. HAZARD IDENTIFICATION

CLASSIFICATION: Not classified according to 29 CFR 1910.1200 (2012)

OTHER HAZARDS: SKIN AND EYE CONTACT: Prolonged contact may cause minor skin or eye irritation. If swallowed can enter lungs and cause damage.

3. COMPOSITION/ INFORMATION ON INGREDIENTS

INGREDIENT

CAS#

WEIGHT

Base Oils

See Below

>99%

*no hazardous ingredients

The Base Oil may contain one or more of the following ingredients: 61788-76-9, 64741-88-4, 64742-01-4, 64742-65-0, 64741-89-5, 64742-48-9, 64742-52-5, 64742-54-7, 64742-56-3, 64742-55-8

COMMON NAMES AND SYNONYMS

Vacuum Pump Oil

There are no stabilizers or impurities that contribute to the classification of the material identified in section 2

4. FIRST AID MEASURES

EYES: Flush with large amounts of water for at least 15 minutes. If redness or irritation persists, contact a physician.

SKIN CONTACT: Wash with soap and water.



SAFETY DATA SHEET

VPO

INHALATION: If inhaled move to fresh air.

INGESTION: Do not induce vomiting. Get medical attention

NOTE TO PHYSICIAN: No specific treatment. Contact Poison Treatment Center if large amounts have been ingested or inhaled

5. FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA: Dry chemical, CO₂, foam, waterfog, sand/earth

SPECIAL FIREFIGHTING PROCEDURES: Wear self-contained breathing apparatus.
Water spray is an unsuitable extinguishing agent.

UNUSUAL FIRE AND EXPLOSION HAZARDS: None

6. ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IN CASE OF RELEASE OR SPILL: Stop leak. Dike up large spills. Use inert absorbent materials such as earth, sand or vermiculite for clean-up. Use personal protective equipment such as gloves, goggles, and coveralls to prevent contact with skin during clean up.

7. HANDLING AND STORAGE

PRECAUTIONS FOR STORAGE AND HANDLING: Avoid exposure to heat and flames. Protect against eye and skin contact. Store containers in an upright and secure position to prevent spills and protect against damage. Prohibit smoking, eating, or drinking in areas where material is handled

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

ENGINEERING CONTROLS

Provide adequate ventilation when working in confined areas

PERSONAL PROTECTIVE EQUIPMENT

SKIN PROTECTION:

General work clothing and gloves (leather) should provide adequate protection. Any contaminated clothing should be promptly removed and washed before reuse.

EYE PROTECTION:



SAFETY DATA SHEET

VPO

For normal conditions, wear safety glasses. Where there is reasonable probability of liquid contact, wear chemical safety goggles.

RESPIRATORY PROTECTION:

None generally required for adequately ventilated work situations. For accidental release or non-ventilated situations, or release into confined space, where the concentration may be above the PEL use a NIOSH approved respirator.

ADDITIONAL RECOMMENDATIONS:

Where contact with liquid is likely, such as in a spill or leak, impervious boots and clothing should be worn.

EXPOSURE LIMITS

OSHA permissible concentration of mineral oil mist in air is 5 mg/m³.

9. PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE:	Clear amber liquid
ODOR:	Petroleum odor
ODOR THRESHOLD:	Not determined
PH:	Neutral
MELTING/FREEZING POINT:	-12°C (10.4°F)
BOILING POINT:	>500°F
FLASH POINT: COC METHOD	148°C (298.4°F)
EVAPORATION RATE:	Negligible
FLAMMABILITY:	Not applicable
LEL/UEL:	Not applicable
VAPOR PRESSURE:	<0.013 kPa (<1 mmHg) at 25°C
VAPOR DENSITY:	>1.0 (air=1)
RELATIVE DENSITY:	0.86 @ 15.6 °C
SOLUBILITY:	Insoluble in water
PARTITION COEFFICIENT n-Octanol/water:	>6
AUTO IGNITION TEMPERATURE:	Not determined
DECOMPOSITION TEMPERATURE:	Not determined
VISCOSITY:	Not Determined

10. STABILITY AND REACTIVITY

STABILITY: STABLE

HAZARDOUS POLYMERIZATION: NONE



SAFETY DATA SHEET

VPO

INCOMPATIBILITY (MATERIALS TO AVOID): Strong oxidizing agents such as chromic acid, hydrogen peroxide and bromine.

HAZARDOUS DECOMPOSITION OR BYPRODUCTS: Upon combustion, CO₂ and CO are generated.

11. TOXICOLOGICAL INFORMATION

INHALATION AND SKIN ABSORPTION HEALTH RISKS: No known significant effects or hazards. OSHA permissible concentration of mineral oil mist in air is 5 mg/m³.

SKIN AND EYE CONTACT: Prolonged contact may cause minor skin and eye irritation.

SYMPTOMS OF EXPOSURE: N/A

INGESTION: Aspiration hazard if swallowed. Can enter lungs and cause damage

ACUTE AND CHRONIC HEALTH HAZARDS: N/A

CARCINOGENICITY: NTP	IARC MONOGRAPHS	OSHA REGULATED
NO	NO	NO

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: N/A

12. ECOLOGICAL INFORMATION

No known significant or critical effects

13. DISPOSAL CONSIDERATIONS

WASTE DISPOSAL METHOD: Dispose of in accordance with Federal, State, and Local regulations.

14. TRANSPORTATION INFORMATION

US DOT ID NUMBER:	None
US DOT PROPER SHIPPING NAME:	None
US DOT HAZARD CLASS:	None
US DOT PACKING GROUP:	None

15. REGULATORY INFORMATION



SAFETY DATA SHEET

VPO

The regulatory information is not intended to be comprehensive. Other regulations may apply to this material.

Federal Regulatory Status

Notification Status

EINECS	All components listed or polymer exempt.
TSCA	All components listed.
DSL	All components listed.

SARA Hazard Categories (311/312)

No SARA 311/312 Hazards.

State Regulatory Status

California Safe Drinking Water and Toxic Enforcement Act (Proposition 65)

This material does not contain any chemicals known to the State of California to cause cancer, birth defects or other reproductive harm.

16. OTHER INFORMATION

HMIS:	H	F	R
	1	1	0

DISCLAIMER

INFORMATION AND RECOMMENDATIONS CONTAINED HEREIN ARE BELIEVED TO BE ACCURATE AT THE TIME OF PREPARATION. NO WARRANTY IS MADE CONCERNING THE ACCURACY AND NO LIABILITY SHALL BE MADE FOR CLAIMS FOR USE OR RELIANCE OF THE RECOMMENDATIONS CONTAINED HEREIN.