

# Safety Data Sheet

# **n-PENTANE**

# 1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

<b>PRODUCT NAME:</b>	n-PENTANE
USE:	Refrigerant additive
<b>CHEMICAL FAMILY:</b>	Paraffin Series Hydrocarbon
<b>DISTRIBUTOR:</b>	National Refrigerants, Inc.
	661 Kenyon Avenue
	Bridgeton, New Jersey 08302

FOR MORE INFORMATION CALL: (Monday-Friday, 8:00am-5:00pm)

1-800-262-0012

IN CASE OF TRANSPORTATION EMERGENCY CALL: CHEMTREC: 1-800-424-9300

**EMERGENCY OVERVIEW:** 

Flammable gas. Liquid under high pressure.

# 2. HAZARDS IDENTIFICATION

CLASSIFICATION: SIGNAL WORD: HAZARD STATEMENT(S): SYMBOL(S): Flammable Liquid DANGER Extremely flammable liquid Flames, Gas Cylinder



### **PRECAUTIONARY STATEMENT(S):**

Prevention: Keep away from heat, sparks, open flame, and hot surfaces. No Smoking

**Response:** Leaking gas fire: Do not extinguish unless leak can be stopped immediately. Eliminate all ignition sources if safe to do so.

Storage: Protect from sunlight, store in a well-ventilated place.

### POTENTIAL HEALTH EFFECTS

#### Inhalation:

Vapors have a mild narcotic effect. Symptoms of overexposure may include drowsiness and irritation of the respiratory passages. Greater exposure may cause unconsciousness and death.

#### **Ingestion:**

Tends to vaporize when swallowed causing aspiration into the lungs. The result can be a rapid fall in oxygen content with asphyxia and consequent brain damage or cardiac arrest.



# Skin Contact:

Causes skin irritation, cracking or flaking due to dehydration and de-fatting action.

#### **Eye Contact:**

Very high vapor concentrations and liquid may cause irritation, redness, and pain.

#### **Chronic Exposure:**

Prolonged skin contact may cause drying, cracking, and dermatitis.

#### **Aggravation of Pre-existing Conditions:**

Persons with pre-existing skin conditions or impaired respiratory function may be more susceptible to the effects of this substance.

3. COMPOSITION / INFORMAT	ION ON INGREDIENTS		
<u>INGREDIENT NAME</u>	CAS NUMBER	<u>WEIGHT %</u>	
n-PENTANE	109-66-0	100	

#### **COMMON NAME and SYNONYMS**

Normal Pentane

There are no impurities or stabilizers that contribute to the classification of the material identified in Section 2

#### 4. FIRST AID MEASURES

#### Inhalation:

Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Call a physician.

#### **Ingestion:**

DO NOT INDUCE VOMITING. Give large quantities of water. Never give anything by mouth to an unconscious person. Call a physician immediately.

#### **Skin Contact:**

Remove any contaminated clothing. Wash skin with soap or mild detergent and water for at least 15 minutes. Wash clothes before reuse. Get medical attention if irritation develops or persists.

### Eye Contact:

Wash thoroughly with running water. Get medical advice if irritation develops.

#### Advice to physician: No special instructions

### 5. FIRE FIGHTING MEASURES

# Fire:

Flash point: -49C (-56F) CC Autoignition temperature: 260C (500F) Flammable limits in air % by volume: lel: 1.5; uel: 7.8

# Extremely Flammable Liquid and Vapor! Vapor may cause flash fire.



#### **Explosion:**

Above flash point, vapor-air mixtures are explosive within flammable limits noted above. Vapors can flow along surfaces to distant ignition source and flash back. Sensitive to static discharge.

#### Fire Extinguishing Media:

Dry chemical, foam or carbon dioxide. Water may be ineffective. Water spray may be used to keep fire exposed containers cool.

#### **Special Information:**

In the event of a fire, wear full protective clothing and NIOSH-approved self-contained breathing apparatus with full facepiece operated in the pressure demand or other positive pressure mode. This highly flammable liquid must be kept from sparks, open flame, hot surfaces, and all sources of heat and ignition. Vapor explosion hazard exists indoors, outdoors, or in sewers.

# 6. ACCIDENTAL RELEASE MEASURES

#### SPILL AND LEAK PROCEDURES:

Contain the spill. Eliminate sources of ignition. Use water spray to reduce vapors. For small spills, take up with absorbent material. If confined space – use self-contained breathing apparatus. Consult local fire authorities.

#### 7. HANDLING AND STORAGE

**NORMAL HANDLING:** Watch for leaks and spills. Bond and ground during liquid transfer. Provide means to control leaks and spills. Protect from sources of ignition. Prohibit smoking in areas of storage or use.

#### **STORAGE RECOMMENDATIONS:**

Keep containers sealed and store in cool, well-ventilated area.

### 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

### **ENGINEERING CONTROLS:**

# PERSONAL PROTECTIVE EQUIPMENT:

#### **SKIN PROTECTION:**

Impervious, insulated gloves recommended. Impervious clothing for prolonged or repeated contact

#### **EYE PROTECTION:**

Face shield or goggles recommended

### **RESPIRATORY PROTECTION:**

NIOSH approved self-contained breathing apparatus for confined areas or areas with poor ventilation.

#### **EXPOSURE GUIDELINES**

(Exposure Limits)

INGREDIENT NAME n-PENTANE ACGIH TLV 600 ppm OSHA PEL 1000 ppm OTHER LIMIT



# 9. PHYSICAL AND CHEMICAL PROPERTIES

**APPEARANCE: PHYSICAL STATE: ODOR:** SOLUBILITY IN WATER @ 70 Deg. F **BOILING POINT:** VAPOR PRESSURE @ 70 Deg. F: FLASH POINT: **EVAPORATION RATE: FLAMMABILITY: LEL/UEL: PARTITION COEFFICIENT n-OCTANOL/WATER: AUTO IGNITION TEMPERATURE: DECOMPOSITION TEMPERATURE:** VISCOSITY: VAPOR DENSITY (air = 1.00): % VOLATILES BY VOLUME: **DENSITY:** pH: **MELTING POINT: SPECIFIC GRAVITY (H2O=1.00): MOLECULAR FORMULA: MOLECULAR WEIGHT:** 

Clear, Colorless liquid with sweet petroleum odor. Liquid at ambient temperature Sweet petroleum odor 0.0385 g / liter 36°C / 97°F 8.6 psia <-40°C (<-40°F) > 1 (Ethyl Ether = 1.0) Extremely flammable 1.5% / 7.8% Log Pow: 3.45 260°C / 500°F Data not available Not applicable 2.5 100% 0.63 g/ml Not applicable -130°C / -201°F 0.631  $C_5H_{12}$ 

72.15

# **10. STABILITY AND REACTIVITY**

### **CHEMICAL STABILITY:**

This product is stable.

# **REACTIVITY:** Not reactive under normal conditions.

#### **INCOMPATIBILITY WITH OTHER MATERIALS:** None

#### **CONDITIONS TO AVOID:**

High Heat, Sparks & Open Flames

# 11. TOXICOLOGICAL INFORMATION

### Acute oral toxicity

Value: LD50 Species: Rat Value in non-standard unit: > 2.000 mg/kg Slightly toxic.

### Acute inhalation toxicity

Value: LC50 Species: Rat



Value in non-standard unit: > 25,3 mg/l Slightly toxic. Acute dermal toxicity Slightly toxic Acute toxicity other routes May be fatal if swallowed and enters airways.

### Skin irritation

Not classified as an irritant. Repeated exposure may cause skin dryness or cracking. May cause dermatitis by skin contact.

# Eye irritation

Not classified as an irritant. May cause mild, short-term discomfort to eyes.

**Sensitization** This substance is not classified as a sensitizer.

### **Repeated dose toxicity**

Not expected to cause damage to organs from prolonged or repeated exposure.

Assessment mutagenicity There is no evidence of mutagenic potential.

### Assessment carcinogenicity

No evidence of carcinogenic effects.

### Assessment toxicity to reproduction

No indication of toxic effects.

# Assessment teratogenicity

No indication of teratogenic effects.

# 12. ECOLOGICAL INFORMATION

### **DEGRADABILITY (BOD):**

#### **Environmental Fate:**

When released into the soil, this material may biodegrade to a moderate extent. When released into the soil, this material is not expected to leach into groundwater. When released into the soil, this material is expected to quickly evaporate. When released into water, this material may biodegrade to a moderate extent. When released to water, this material is expected to quickly evaporate. When released into the water, this material is expected to have a half-life of less than 1 day. This material has an estimated bioconcentration factor (BCF) of less than 100. This material has a log octanol-water partition coefficient of greater than 3.0. This material is not expected to significantly bioaccumulate. When released into the air, this material is expected to be readily degraded by reaction with photochemically produced hydroxyl radicals. When released into the air, this material is expected to have a half-life between 1 and 10 days.

### **Environmental Toxicity:**

No information found.



# **13. DISPOSAL CONSIDERATIONS**

Disposal must comply with federal, state, and local disposal laws

<b>US DOT ID NUMBER:</b>	UN 1265	
US DOT SHIPPING NAME:	PENTANES	
US DOT HAZARD CLASS:	3	
<b>US DOT PACKING GROUP:</b>	II	

The ingredients listed in section 2 are reported/included in the U.S. TSCA inventory and Canadian domestics substance list.

### **16. OTHER INFORMATION**

**OTHER INFORMATION:** HMIS Classification: Health – 1, Flammability – 4, Reactivity – 0

#### **DISCLAIMER:**

National Refrigerants, Inc. believes that the information and recommendations contained herein (including data and statements) are accurate as of the date hereof). NO WARRANTY OF FITNESS OR ANY PARTICULAR PURPOSE, WARRANTY OF MERCHANT ABILITY, OR ANY OTHER WARRANTY, EXPRESSED OR IMPLIED, IS MADE CONCERNING THE INFORMATION PROVIDED HEREIN. The information provided herein relates only to the specific product designated and may not be valid where such product is used in combination with any other methods of use of the product and of the information referred to herein are beyond the control of National Refrigerants. National Refrigerants expressly disclaims any and all liability as to any results obtained or arising from any use of the product or reliance on such information.